PCA Autocross Safety Inspection

May 2020

It is the sole responsibility of each participant to present a vehicle that is safe to operate in an autocross event and is in sound mechanical condition. Safety inspection by PCA Region volunteers <u>does not relieve the participant of their responsibility</u> for the safety of the vehicle they have entered.

- € Helmet meets current or two prior SA, M, or K Snell ratings. Helmets built to Snell Foundation Standards or other standards such as FIA 8860, SFI 31.1 and BS6658-85 Type A-FR are approved.
- € **Helmet** is in good physical shape. Liner is not loose inside. Straps are not frayed. No obvious outer shell damage. Drivers of cars with no windshields must have eye protection.
- € Gas Cap securely in place
- € Seatbelts must be in good condition and not overly worn, frayed, or stiff. 5 or 6-point racing harnesses must be installed per manufacturer's instructions. If non-factory upper restraints are installed in open cars, factory roll over protection or aftermarket roll bar/cage must be installed.
- € Seats are properly attached and functional
- € Wheels must be free of cracks and all fasteners installed on all wheels
- € **Tires** must have no cord showing at any time and be free of cracks
- € Throttle operates properly
- € Brake pedal must not go to the floor without any resistance
- € Brake rotors or drums must not be cracked to the edges
- € Brake fluid must be between the minimum and maximum level in the reservoir (if visible)
- € Fluid leakage must not be significant
- € Battery must be attached securely to the frame or chassis
- € Final Prep: All loose objects inside the passenger compartment or trunk(s) must be removed. Cameras <u>must</u> be securely mounted.